



SPECTRA FUELS

Spectra Fuels - Bunkering at Worldwide Ports  
Email us: bunkers@SpectraFuels.com Call us: +91 9920447859

ISO 8217: 2012

RMG 380

Characteristic	Unit	Limit	RMG 380
Density at 15°C	kg/m <sup>3</sup>	Max.	991
CCAI	-	Max.	870
Kinematic viscosity at 50°C	mm <sup>2</sup> /s <sup>a</sup>	Max.	380
Flash Point	°C	Min.	60,0
Pour Point (upper) <sup>b</sup>			
-Winter quality	°C	Max.	30
-Summer quality			30
Carbon residue: Micro Method	Mass %	Max.	18,00
Ash	Mass %	Max.	0,100
Water	Volume %	Max.	0,50
Sulfur <sup>c</sup>	% (m/m)	Max.	Statutory Requirements
Sodium	mg/kg	Max.	100
Vanadium	mg/kg	Max.	350
Total sediment aged	Mass %	Max.	0,10
Aluminium plus Silicon	mg/kg	Max.	60
Used lubricating oil (ULO)	mg/kg		The fuel Shall be free from ULO. A fuel shall be considered to contain ULO when either one of the following conditions is met:  Calcium> 30 and Zinc > 15; or Calcium> 30 and Phosphorus >15
Calcium and Zinc, or Calcium and Phosphorous			



SPECTRA FUELS

Spectra Fuels - Bunkering at Worldwide Ports  
Email us: bunkers@SpectraFuels.com Call us: +91 9920447859

ISO 8217: 2012

RME 180

Characteristic	Unit	Limit	RME 180
Density at 15°C	kg/m <sup>3</sup>	Max.	991
CCAI	-	Max.	870
Kinematic viscosity at 50°C	mm <sup>2</sup> /s <sup>a</sup>	Max.	180
Flash Point	°C	Min.	60,0
Pour Point (upper) <sup>b</sup>			
-Winter quality	°C	Max.	30
-Summer quality			30
Carbon residue: Micro Method	Mass %	Max.	18,00
Ash	Mass %	Max.	0,100
Water	Volume %	Max.	0,50
Sulfur <sup>c</sup>	% (m/m)	Max.	Statutory Requirements
Sodium	mg/kg	Max.	100
Vanadium	mg/kg	Max.	350
Total sediment aged	Mass %	Max.	0,10
Aluminium plus Silicon	mg/kg	Max.	60
Used lubricating oil (ULO)	mg/kg		The fuel Shall be free from ULO. A fuel shall be considered to contain ULO when either one of the following conditions is met:  Calcium > 30 and Zinc > 15; or Calcium > 30 and Phosphorus >15
Calcium and Zinc, or Calcium and Phosphorous			



SPECTRA FUELS

Spectra Fuels - Bunkering at Worldwide Ports  
Email us: bunkers@SpectraFuels.com Call us: +91 9920447859

ISO 8217: 2012

DMA

Characteristic	Unit	Limit	DMA
Density at 15°C	kg/m <sup>3</sup>	Max.	890,0
Kinematic Viscosity at 40°C	mm <sup>2</sup> /sb	Min.	6,000
		Max.	2,000
Flash Point	°C	Min.	60,0
Pour Point (upper) <sup>b</sup>			
-Winter quality	°C	Max.	-6
-Summer quality			0
Hydrogen Sulfide	mg/kg	Max.	2,00
Cloud Point	°C	Max.	-
Sulfur b	Mass %	Max.	Statutory Requirements
Cetane Index	-	Min.	40
Carbon residue on 10% Volume distillation residue	Mass %	Max.	0, 30
Carbon Reside: Micro Method	Mass %	Max.	-
Cloud Point	°C	Max.	-
Ash	Mass %	Max.	0,010
Total sediment by hot filtration	Mass %	Max.	-
Water	Volume %	Max.	-
Acid Number	mg KOH/g	Max.	0,5
Lubricity, corrected wear scar diameter (wsd 1,4) at 60 °C <sup>h</sup>	µm	Max.	520
Oxidation Stability	g/m <sup>3</sup>	Max.	25